

"Express Mail" mailing label number EL582470228US

Date of Deposit August 21, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated and is addressed to the Commissioner of Patents and Trademarks, Washington, D. C. 20231.

Carole A. Quinn
(Typed or printed name of person mailing paper or fee)

Carole A. Quinn
(Signature of person mailing paper or fee)

DATA INDEXING USING BIT VECTORS

This application claims the benefit of U.S. Provisional Application No. 60/149,855, filed August 19, 2000.

BACKGROUND OF THE INVENTION

Field Of The Invention

The present invention relates to indexing data and, more particularly, to a method and apparatus wherein bit vector indexing is used to index data such as record data in a database.

Description Of The Related Art

A DBMS (Database Management System) is used to manage data and is comprised of computer-executable code that may be used to define

the structure of data and to access data within the defined structure. One example of a DBMS is a relational DBMS, or RDBMS. An RDBMS manages tables that make up a relational database as well as the data contained in the tables. In an RDBMS, data is organized in rows (or records) and columns (or fields) of the tables, and two or more tables may be related based on like data values. The intersection of a row and column in a table is referred to as a cell and contains the data value for a particular field of a particular record.

A DML (data manipulation language) such as SQL (Structured Query Language) is typically used to store, retrieve and modify data in a table. A schema defines the structure of a database, i.e., each table and the fields within a record of a table. A schema is itself considered data that is stored in one or more tables. Therefore, like other data in a database, a DML may be used to store, retrieve and modify the data in the database as well as the structure of a database.

There are performance issues with respect to data access in a DBMS particularly when the database is very large. A typical RDBMS is optimized for certain types of query access. However, performance degrades when the database is very large, when a query returns a large set of records, when row selection criteria apply across multiple fields and tables, or when interactively browsing large sets of query results. Value limiting on a lookup table reduces the set of lookup

values by eliminating from the set of all possible lookup values those values that do not correspond to any records in the primary table. Another problem is that value limiting cannot efficiently and quickly be done using the standard mechanisms of an RDBMS.

An RDBMS uses indexes to assist in performing queries and quickly locate records in the database. Indexes store one or more field (or column) values from each record as a unique key for the record. Indexes do an adequate job of speeding up the query process even on large databases when the row selection criteria include constraints on only a single field and when the query results do not need to be browsed interactively. In particular, an RDBMS can quickly search for and retrieve an individual record from among even millions of records based on the value of an indexed field.

Unfortunately, however, there are a number of shortcomings to searching using conventional forms of indexing.

For example, if the number of records in the database is very large, the index itself can become large as well, so that as a practical matter it will be stored on disk rather than in memory, moderately increasing the time necessary to search for records.

Further, if the row selection criteria includes constraints for multiple fields, the

5

10

30

SUMMARY OF THE INVENTION

The present invention addresses the foregoing problems and provides for an indexing scheme for indexing data in data records using bit vectors.

In one aspect of the invention, indexing of occurrences of a value in at least one data record using a bit vector representation is provided wherein the bit vector representation is associated with the value and a bit of the bit vector representation is associated with each of the at least one data record, a determination is made whether the value exists in the at least one data record, a bit value is assigned to the bit in the bit vector representation based on the outcome of the determination.

Indexing using BVs (bit vectors) provide several advantages over conventional indexing approaches. Since, a BV uses one bit per record in the primary table instead of a minimum of eight bytes per record for an index, a bit vector is substantially smaller than a conventional index. This results in faster processing and less memory usage, since it is not likely to need to be stored on disk, and if it is, requires that less data be accessed on the disk for a particular operation. Further, it is possible to encode a BV, using any of the well known compression schemes, to further reduce the amount of storage they require.

5

10

15

25

completely eliminate the need to perform complex multi-table joins.

In another aspect of the invention, combinations of values used in at least one data record are identified by creating a first bit vector representation for a first value, the first bit vector representation identifying use of the first value in the at least one data record, creating a second bit vector representation for a second value, the second bit vector representation identifying use of the second value in the at least one data record, and performing a bit-level operation on the first and second bit vector representations.

This brief summary has been provided so that the nature of the invention may be understood quickly. A more complete understanding of the invention can be obtained by reference to the following detailed description of the preferred embodiment(s) thereof in connection with the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an outward view of a hardware environment embodying the present invention.

Fig. 2 is a block diagram of the internal architecture of a typical computer for use in conjunction with the present invention.

Fig. 3 provides an example of a table and the use of BVIs to index data contained in the table according to the present invention.

Fig. 4 further illustrates the BVs (bit vectors) depicted in Fig. 3.

Fig. 5 provides a diagram of process steps to create a BVIs and BVs according to the present invention.

Fig. 6 provides a diagram of process steps to perform a bit-wise operation on BVs according to the present invention.

Figs. 7A and 7B provide an example of bit-wise "OR" and "AND" operations performed on BVs according to the present invention.

Fig. 8 provides a diagram of process steps to perform value-limiting according to the present invention.

Figs. 9A and 9B provide an example of value-limiting processing performed according to the present invention.

Fig. 10 provides an example of Category-Manufacturer and Manufacturer-Category BVIs according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 is an outward view of representative computing hardware embodying the present invention. Shown in Fig. 1 are computer 10 executing an operating system, display monitor 11 for displaying text and images to a user, keyboard 14 for entering text and commands into computer 10, and mouse 12 for manipulating and for selecting objects displayed on display monitor 11, or for

output to an output device such as printer 16. Also included with computer 10 are fixed disk drive 6, in which are stored application programs, such as a DBMS and other applications, data files, and device drivers for controlling peripheral devices attached to computer 10, floppy disk drive 15 for use in reading data from and writing data to floppy disks inserted therein. Data and/or applications may also be accessed from a CD-ROM via a CD-ROM drive (not shown) or over a network to which computer 10 may be connected (network connection not shown).

Fig. 2 is a block diagram of the internal architecture of computer 10. Shown in Fig. 2 are CPU 20, which may be any microprocessor including, but not limited to, a Pentium-type microprocessor, interfaced to computer bus 21. Also interfaced to computer bus 21 are printer interface 25, to allow computer 10 to communicate with printer 16, modem interface 29 to enable communications between computer 10 and a modem, display interface 27 for interfacing with display monitor 11, keyboard interface 28 for interfacing with keyboard 14, mouse interface 23 for interfacing with mouse 12, and network interface 26 for connecting to a network (e.g., Internet, intranet, local area network, etc.).

Read only memory (ROM) 24 stores invariant computer-executable process steps for basic system functions such as basic I/O, start up, or reception of keystrokes from keyboard 14.

Main random access memory (RAM) 30 provides CPU 20 with memory storage which can be accessed quickly. In this regard, computer-executable process steps of a DBMS or other application are transferred from disk 6 over computer bus 21 to RAM 32 and executed therefrom by CPU 20.

Also shown in Fig. 2 is disk 6 which, as described above, includes a windowing operating system, a DBMS which includes data stored therein as well as schema and data stored in one or more tables defined in the schema. Further, disk 6 may be used to store executable-code (e.g., stored procedures) comprising steps described herein indexing data using bit vector representations. Disk 6 further includes data files and device drivers as shown.

The present invention uses a BVI (Bit Vector Index) to augment the standard indexing scheme of a typical RDBMS. A BVI is a collection of BV representations that together comprise an index for a particular column in a table of a database. One example of a BV representation is a bit vector (BV) comprising a sequence of Boolean values, each stored as a single bit. The column in the indexed table stores a reference to a value in a set of enumerated values such as those values found in a lookup table. A lookup mechanism uses a pair of matching columns from two tables, taking the value of the column for a single record in the first table

to "look up" additional information in a single
corresponding record in the second (lookup) table.

The present invention creates a BVI for
each matching column pair that relates a lookup
5 field in the indexed table to a set of values in a
lookup table. BVI indexing of the present invention
may be used in place of or as a supplement to other
forms of indexing.

BVIs and BVs have a number of advantages.
10 Since, a BV uses one bit per record in the indexed
table instead of a minimum of eight bytes per record
for an index, a bit vector is substantially smaller
than a conventional index. This results in faster
processing and less memory usage, since a BVI is not
15 likely to need to be stored on disk, and if it is,
requires that less data be accessed on the disk for
a particular operation. Further, it is possible to
encode a BV to generate another BV representation
that optimizes the space need for a BV. Further, it
20 is possible to compress a BV representation
(optimized or not), using any of the well known
compression schemes, to further reduce the amount of
storage required for a BVI.

Further, instead of complex algorithms
25 reconciling individual sets of query results to
combine the multiple constraints; logical operations
may be used. Unlike the geometric time required to
reconcile individual result sets in the conventional
searching approaches, the time grows linearly with
30 the number of records in the primary table.

information associated with a particular manufacturer and category. The manufacturer and category fields are lookup fields such that the value in each cell stores a reference (or identifier, ID) to a value in a lookup table.

INS. 31 > Lookup tables 301 and 302 associate the reference made in records 310 through 314 to an actual value. Table 301 contains values for manufacturers while table 302 contains category values. Referring to table 301, for example, an ID value of "2" corresponds to the manufacturer, "APEX". In products table 300, records 312 and 315 have a value of "2" in the manufacturer field. In a DBMS, the value in the manufacturer field of record 312, for example, may be used to lookup the name of the manufacturer associated with a lookup value of "2". Similarly, a value in the category fields of records 310 through 314 may be used to identify a corresponding category name stored in table 302.

BVIs 303 and 304 contain BVs associated with the manufacturer table 301 and category table 302 (respectively).

A BVI may comprise multiple BVs. Preferably, a BVI such as BVIs 303 and 304 are array structures with each entry containing a BV and the indexed value being a pointer into the array. Further, a BVI is preferably a unidimensional array. However, a BVI may be multidimensional arrays as well. BVIs 303 and 304 of Fig. 3 are depicted as two dimensional arrays that includes the indexed

00643316 002100

value to further illustrate the functionality of the present invention.

Each BV of a BVI identifies the records in the indexed table that correspond to one particular value in the lookup table. A bit is set in a particular position in the BV that corresponds to a given value, if the corresponding record in the indexed table has that value. The collection of BVs for all of the values of the matching column in the lookup table comprises the BVI for that matching column pair.

Thus, for example, records 330 through 332 of BVIs 303 contain BVs that provide an index of records 310 through 314 and the manufacturers identified in the records. Similarly, records 340 through 342 contain BVs for indexing records 310 through 314 by category.

Fig. 4 further illustrates the BVs depicted in Fig. 3. BVs 430 through 432 provide an index of manufacturers while BVs 440 through 442 index categories. To further illustrate, BV 430 contains five bits each corresponding to a record 310 through 314 of table 300. The leftmost bit corresponds to record 310, the next to record 311, the third to record 312, the fourth to record 313 and the rightmost bit to record 314.

In this example, a value of "1" in a manufacturer's BV indicates that the corresponding record in table 300 references the manufacturer that corresponds to the BV in its manufacturer field.

5

10

15

25

Compression is especially useful where there are contiguous portions of a BV with like values (i.e., "0"s or "1"s). However, even in the case that a BV contains randomly distributed 1's or 0's, it may be possible to compact the BV by storing bits up to the last bit set.

The present invention provides various encoding mechanisms to optimize storage based on the nature of the BVs. A flag may be associated with each BVI to identify the encoding scheme used for a BVI.

One such BVI structure may be used where there are contiguous portions of a BV, the BV may be stored as an ordered list of either set (e.g., values of "1") or unset bits (e.g., values of "0"). That is, instead of storing a BV as a series of "1"s and "0"s, bit position information is stored. For example, where the first ninety-nine bits are "0" and the hundredth bit is a "1", the first entry in the BV is the value "100". Conversely, where the BV contains fewer "0"s than "1"s, for example, the ordered list may indicate the position of the "0"s in the BV. Such encoding is especially useful where the number of bits set (or unset) is less than 1 in each "n" bits where "n" is the word size (or number of bits used to store a number). For example, such encoding is well suited for BVs where the number of bits set (or unset) is 1 bit in 32 bits for 4-byte numbers, 1 in 16 for 2-byte numbers, 1 in 8 for 1-byte numbers, etc.

A BV may also be stored as ordered start and end pairs of set (or unset) bits. That is, a run of set (or unset) bits are stored as start and stop positions within a BV in which the run begins and ends (respectively). Such encoding is especially useful when the average run, or region size, is greater than twice the word size used to store a number, or a region size of 64 for 4-byte numbers, 32 for 2-byte numbers, etc.

Compression can also be applied to any of the above encoding approaches. However, there are tradeoffs between speed and storage. Compression can act to decrease speed, but is useful where it improves storage. The determination may be made based on the available computer system resources.

As with standard indexes, there is a mapping between a bit of the BV and a record in the indexed table. Preferably, the pointer into a BV is a field in the indexed table (e.g., a record ID field such as the product ID field in table 300) whose value identifies the corresponding bit position in the BV. Alternatively, a mapping mechanism may be used to translate between a record ID and a position in a BV.

A BVI must be synchronized with the fields that it indexes. For an existing table, the values contained in the indexed fields are used to generate a BVI. Thereafter, the BVI is updated whenever a value in the indexed field is modified.

Fig. 5 provides a diagram of process steps to create a BVI and BVs contained therein according to the present invention. The process steps of Fig. 5 are performed for each value in a lookup table (e.g., values 1 through 3 in table 301 or 302) to generate a BVI where a BV in the BVI corresponds to a value in the lookup table.

At step S500, a determination is made whether all of the enumerated values in the lookup table have been processed. If so, processing ends at step 506. If not, processing continues at step S501 to generate a BV for the next enumerated value.

At step S501, the BV for the next enumerated value is initialized. At step S502, a determination is made whether all of the records in the indexed table have been processed for the current enumerated value. If so, processing continues at step S500 to process any remaining enumerated values. If not, processing continues at step S503 to get the enumerated value used in the next record in the indexed table (e.g., one of records 310 through 314 of products table 300).

At step S504, a determination is made whether the value used in the record is the same as the indexed value currently being processed. If not, processing continues at step S502 to process any remaining records in the indexed table. If so, processing continues at step S505 to set the bit, that corresponds to the current record, in the BV for the indexed value currently being processed.

Processing continues at step S502 to process any remaining records in the indexed table.

Searching lookup fields based on lookup values is dramatically faster using a BVI than a traditional index. To identify the set of records in the indexed table that correspond to a particular value in the lookup table, the BV for that value is extracted from the BVI for the lookup table. The bits that are set in the BV immediately identify the set of records. Using this approach, the time required to identify the set of records having a particular value in a lookup field grows linearly rather than geometrically (as in conventional approaches) with the number of records, as well as linearly rather than exponentially (as in conventional approaches) with the number of tables.

In addition, multiple constraints on a single lookup field may be handled using logical operations on BVs. Thus, for example, selecting records based on multiple lookup table values is accomplished using an "OR" operation. Such an operation may be used to select records from products table 300 where the manufacturer is either "ACME" or "Apex". The BVs that correspond to each of the desired lookup table values are "ORed" together. Any bit that is set in the resulting BV indicates that the corresponding record in the indexed table is included in the result set.

Fig. 6 provides a diagram of process steps to perform a bit-wise operation on BVs according to

the present invention. At step S601, a result BV is initialized to the first BV to be used in the operation. At step S602, a determination is made whether all operations have been performed. If so, processing ends at step S605. If not, processing continues at step S603, to get the next BV. At step S604, the result BV is updated by performing a bit-wise operation (e.g., an "OR" or "AND" operation) on the result BV and the BV retrieved in step S603. Processing then continues at step S602 to process any remaining BVs and or BVIs.

Operations performed on BVs may proceed hierarchically in addition to the linear approach taken in Fig. 6. That is, for example, operations performed on like BVs are performed first using an "OR" bit-wise operation and bit-wise "AND" operations on dissimilar BVs are performed on the result(s). To illustrate, consider a selection criteria that comprises "Printer" or "Monitor" from either "ACME" or "Apex". Since the first two are both categories of products and the latter two are both manufacturers, a bit-wise "OR" operation is performed to generate a BV that satisfies the category criteria, a bit-wise "OR" operation is performed to generate a BV that satisfies the manufacturer criteria, and the two generated BVs are then bit-wise "ANDed".

Figs. 7A and 7B provide an example of bit-wise "OR" and "AND" operations performed on BVs within BVIs according to the present invention.

Referring to Fig. 7A, an "OR" operation is performed on the "ACME" and "Apex" BVs (from records 330 and 331 of table 303) to identify the records in products table 300 where the manufacturer is either "ACME" or "Apex".

BV 700 from record 330 is "ORed" with BV 701 of record 331 to yield BV 702. Since a value of "1" is used to indicate that the corresponding record in the products table 300 contains the lookup table value (i.e., either "ACME" or "Apex"), the presence of a "1" in BV 702 indicates that either "ACME" or "Apex" appears in the corresponding record. That is, records 310, 311, 312, and 314 contain a manufacturer's value of either "ACME" or "Apex".

BVIs also facilitate searching that involve constraints on multiple fields. In a conventional approach, complex algorithms are used, and reconciling individual sets of query results must be performed to combine the multiple constraints. Instead, the present invention contemplates one or more operations on a set of BVIs that is faster and less complex. After the bit vectors for multiple values constraining a single lookup field are first bit-wise "ORed", the resulting BVs for each of the lookup fields are then bit-wise "ANDed". Unlike the geometric time required to reconcile individual result sets, the time grows linearly with the number of records in the indexed table.

For example, a request for a manufacturer equal to either "ACME" or "Apex" and a category of "Computer" may be satisfied using logical bit-wise operations (e.g. "AND" and "OR") on the corresponding manufacturer and category BVIs.

The appropriate manufacturer BVs are bit-wise "ORed" together as illustrated in Fig. 7A. The result, BV 702, is then bit-wise "ANDed" with the BV corresponding to the "Computer" category. Referring to Fig. 7B, BV 702 is bit-wise "ANDed" with BV 711 (from record 341) to yield BV 712. As indicated by BV 712, records 311 and 312 contain the requested "ACME" and "Apex" computer products.

In the above operations, there was no need to store query (e.g., intermediate or final) results in temporary storage (e.g., file or memory). Further, the appropriate records may be found without the need to access the records themselves. The records that correspond to the set values in the result BV values are the appropriate records. Given records must be accessed only when it is necessary to provide the information contained in the record such as when the record is to be displayed in an interactive environment (e.g., browsing environment). Since the time needed to retrieve all of the records to perform the necessary queries as done in the past is eliminated, the setup time needed to generate the interactive display may be reduced. Records are only accessed when they are to

0044346-08400

5

10

20

25

30

which records exist in the indexed table, not just the values already selected based on constraints on the value-limited lookup field.

5 If one does not already exist, an intermediate BV is generated using the constraints on any other lookup fields.

10 A logical "AND" operation is then performed on the intermediate BV and each BV in the BVI for the value-limited lookup field. In contrast to a bit-wise "AND" operation, a logical "AND" returns a single value (i.e., either "TRUE" or "FALSE"). Any value for which the result of the logical "AND" is "FALSE" may be eliminated from the value-limited list. Note that it is not always
15 necessary that all the bits in the BV be compared. That is, the comparison can stop as soon as one pair of corresponding bits are found to both be set.

20 Fig. 8 provides a diagram of process steps to perform value-limiting according to the present invention. Initially, the constraints on the value-limited field are ignored and, at step S801, the set of valid values for the value-limited field are all the values.

25 At step S802, a determination is made whether constraints on other lookup value fields have been processed. If not, processing continues at step S803 to generate or update a limiting BV using the next constraint. The limiting BV is used to limit the value-limited field by applying it to
30 each of the BVs in the value-limited field's BVI.

5 If it is determined, at step S802, that
all other constraints have been processed,
processing continues at step S804 to determine
whether all values in the value list initially
created in step S801 have been processed. If so,
10 processing ends at step S805. If not, processing
continues at step S806, to get the BV that
corresponds to the next value in the value list. At
step S807, a logical "AND" operation is performed on
the value BV and the limiting BV generated in step
15 S803.

Figs. 9A and 9B provide an example of value-limiting processing performed according to the present invention. Fig. 9A provides an example of value-limiting manufacturers to those that provide computer products. Initially, a value list 900 is

A result BV is generated which, in the case of the example, is simply the BV for "Computers", or BV 941 (i.e., "01100"). BV 941 is logical "ANDed" with each of BVs 930, 931 and 932 from the manufacturer BVI table 303. BV 930 (for manufacturer ID="1" or "ACME") is logical "ANDed" with BV 941 to yield BV 951. As illustrated by BV 951, the result of a logical "AND" is "TRUE", since both BVs 930 and 941 have the second bit set. Similarly, a logical "AND" between BV 931 (for manufacturer ID="2" or "Apex") and BV 941 results in "TRUE". However, BV 932 (i.e., for manufacturer ID="3" or "Best") logically "ANDed" with BV 941 yields no set bits (as illustrated by BV 953). Therefore, the result of the logical "AND" is "FALSE". As indicated in value list 901, the value limited set of manufacturers is "ACME" (ID="1") and "Apex" (ID="2"). A validation check of the data will reveal that the only manufacturers with computer products are "ACME" and "Apex".

Similarly, Fig. 9B illustrates value-limiting performed on the category lookup field. To find the valid categories for the "ACME" manufacturer, for example, a result BV is generated while ignoring the Category constraints. In this case, this is simply BV 930 (i.e., "11000") from the manufacturers BVI. BV 930 is logical "ANDed" with

each of the category BVs 940, 941 and 942. As illustrated by BVs 954, 955 and 956, logical "AND" operations yield a "TRUE" for ID="1" and ID="2", but a "FALSE" for ID="3". Thus, as indicated in value list 901, the valid categories are "Printers" and "Computers".

Like BVIs 303 and 304 that store BVs for an indexed value relative to data records, it is also possible to create value-limiting BVIs that store BVs to identify a correlation between BVIs. Thus, for example, it is possible to create a Category-Manufacturer BVI that includes BVs that correlate each of the categories with each of the manufacturers. Thus, examination of one of the BVs in the Category-Manufacturer BVI identifies which manufacturers sell what product category (or categories). Similarly, it is possible to create a Manufacturer-to-Category BVI to identify which product category (or categories) are offered by a particular manufacturer.

Fig. 10 provides an example of Category-Manufacturer and Manufacturer-Category BVIs according to the present invention. Each BV in BVI 1000 identifies the manufacturers that offer a given product category. A bit in a BV of BVI 1000 correlates a category with a manufacturer. For example, bit 1012 correlates the "Apex" manufacturer with the "Computer" category. Similarly, each BV in BVI 1001 identifies the product categories offered by a given manufacturer. Each bit (e.g., bit 1013)

correlates a manufacturer (e.g., "Apex") and a category (e.g., "Computer").

5 As discussed above, a BV that reflects occurrences of values in an indexed table such as products table 300 is updated to reflect a change made to a record in the indexed table (e.g., products table 300). A change in a BV of a retained value-limiting BVI may also be necessary.

10 For example, assume that the Category ID in record 312 is changed from "2" to "1". BVs 340 and 341 are updated as well to reflect the change as is illustrated in BVs 1340 and 1341, respectively. The inquiry then becomes whether or not BVIs 1000 and 1001 should also be updated. The third bit of
15 BV 1340 is updated to indicate that an additional record of products table 300 refers to Category ID="1". Similarly, the third bit of BV 1341 is updated to reflect that record 312 in products table 300 refers has been changed to Category ID="1".

20 The focus of inquiry with respect to value-limiting BVIs 1000 and 1001 is whether or not the intersections of Category ID="2" and Manufacturer ID="2" need to be updated. Bit 1014 of BVI 1000 and bit 1015 of BVI 1001 should reflect the
25 newly-created relationship while bit 1012 of BVI 1000 and 1013 of BVI 1001 of BVI 1001 reflect the relationship severed by the update. Updating these bits is based on whether there are other records in products table 300 that include both a Category ID
30 and a Manufacturer ID equal to "2". Instead of

001220 "344960

5 Bits 1014 and 1015 correspond to a
combination of Category "1" and Manufacturer "2",
and the change to products table 300 created a
relationship between these values. If another
record contains this relationship, bits 1014 and
10 1015 are already set. However, bits 1014 and 1015
are unset indicating that there is no prior
relationship between these values of Category and
Manufacturer. Bits 1014 and 1015 are therefore set
to reflect the newly-created relationship.

15 Bits 1014 and 1015 may simply be set.
Alternatively, a logical "AND" may be performed
between the updated BV 340 (i.e., BV 1340, "10110")
and BV 331 (i.e., "00101"). The result of the
logical "AND" reflects the fact that the update
20 created a combination of Manufacturer and Category
that did not previously exist. Bits 1014 and 1015
are updated to reflect the new combination.

In contrast to bits 1014 and 1015 that
involve the relationship created by the update, bits
25 1012 and 1013 involve the relationship severed by
the update. What is not immediately apparent is
whether there is another record in products table
300 that contains the same relationship (i.e.,
Category "2" and Manufacturer "2"). If not, bits
30 1012 and 1013 need to be reset. If there is another

relationship, however, there is no need to update bits 1012 and 1013.

The simple (but inefficient) approach is to simply run through the records to see if any records match. An alternative approach is to first update BVI 304 (i.e., BVs 340 and 341 are updated as BVs 1340 and 1341) to reflect the update to products table 300. Once BVI 304 is updated, BV 1341 (i.e., "01000") from BVI 304 is logical "ANDed" with BV 331 ("00101") of BVI 303 to determine whether any records meet both the Category "2" and Manufacturer "2" criteria after the update. If the result is "TRUE", there is no need to update bits 1012 and 1013. If the result is "FALSE", bits 1012 and 1013 are unset.

In the value-limiting examples discussed above, an "AND" operation is performed to limit one value set by another value set. Value-limiting may be used to limit the value selections made available to a user. Thus, given a particular value for Manufacturer (e.g., "ACME"), value-limiting may be used to identify those Category values that are associated in one or more records of the products table 300. In addition to "AND", it is possible to "OR" BVs to identify existing value combinations or lack thereof.

The present invention performs bit-level operations such as the bit-wise and logical operations described above. It is possible to further optimize these operations by storing the

US 4,343,400

5
10

15